BERICAP Technology

closures for containers with standard threaded necks and DIN thread profiles









BERICAP Technology Closures for the blow moulded industry

Fittings for venting and breathing

Plastic containers are sensitive to changes in temperature, pressure and altitude. These changes can trigger chemical reactions in the product or cause it to deteriorate, sometimes leading to violent release of gases. This in turn may result in leakages, or cause the packaging to collapse or become deformed. Vent fittings allow gas exchange and provide protection against contamination. Whatever the requirements, BERICAP offers a wide range of vented fittings for its closures.

GORE™ Packaging Vents offer the best combination of liquid resistance and airflow through the use of expanded polytetrafluoroethylene (ePTFE). The material's microporous nature allows airflow and equalizes pressure, even after contact with high viscosity or low surface tension liquids.





Allows breathing, prevents leakage





Flow control for greater customer convenience


ANTIGLUG

The ANTIGLUG pouring device is a unique neck-insert which presents air-locks

- Exact pouring precise pouring from container to targeted aperture
- Easy measure steady flow of liquid eases the measuring process
- No loss
 easy and complete emptying reduces
 potential loss of liquid and reduces
 hazardous waste
- No spilling reduces unwanted splashing









TAP BERIFLOW

- An important and helpful accessory with high chemical resistance mainly used in the cleaning, chemical and automotive industry.
- Fast, clean dispensing with a flow rate of more than 5L/min without gurgling.
- The outlet spout fits onto DIN 28 bottle necks and its chamfered tip for clean dispensing allows easy dosing even in smaller container (re-fill).
- Available for DIN 45 / 55 and 60 neck finish.
- All components are physiologically harmless.



BERICAP Technology Closures for the blow moulded industry

	TE-Band	DIAM	Resin	Thread	Wadding	UN Qualification	Flow Control/ ANTIGLUG	GORE™ Membrane	CR- Certificate
SK 42/21 SFB MDS	SFB	42mm	HDPE	DIN 42	EPE	YES	NO	NO	
SK 42/21 SFB MK	SFB	42mm	HDPE	DIN 42	Bore Seal	NO	NO	NO	
SK 45/26 MAB MDR	MAB	45mm	HDPE	DIN 45	EPE	YES	YES	YES	
SVB 45/28 MAB	MAB	45mm	HDPE/EVA	DIN 45	EVA	NO	YES	NO	
SK 45/27 MAB MDR CR	MAB	45mm	HDPE	DIN 45	EPE	YES	YES	YES	ISO 8317
SK 55/27 MAB MDR	MAB	55mm	HDPE	DIN 55	EPE	YES	YES	YES	
SK 60/31 MAB MDR	MAB	60mm	HDPE	DIN 60	EPE	YES	YES	YES	
SK 60/31 MAB IHS	MAB	60mm	HDPE	DIN 60	Aluminium induction heat seal	YES	NO	NO	-
SVB 60/32 MAB	MAB	60mm	HDPE/EVA	DIN 60	EVA	NO	NO	NO	
SK 60/33 MAB MDR CR	MAB	60mm	HDPE	DIN 60	EPE	YES	YES	YES	ISO 8317

High quality caps, dispensing aids and vent fittings are needed for:

Food, dressings, automotive products for garages, detergents for cleaning or chemicals for hospitals the packing you use must meet the highest standards and closures have to be produced in a clean environment.













Liquids for the food industry